

40 W SOLAR PANEL

**Domestic &
INDUSTRIAL
PURPOSES**

40 W Solar Panel

- Model : AWSS40W
- Maximum Power at STC (P_{max}) : 40W
- Optimum Operating Voltage (V_{mp}) : 17.5V
- Optimum Operating Current (I_{mp}) : 2.289A
- Open-Circuit Voltage (V_{oc}) : 21.60V
- Short-Circuit Current (I_{sc}) : 2.572A
- Operating Temperature : (-40 to 80°C)
- Maximum System Voltage : DC 1000
- Maximum Series Fuse Rating : 15A
- Power Tolerance : +/- 3%

STC : Irradiance 1000W/m²

Modules Temperature : 25°C

A_m : 1.5



Mechanical Characteristics

- Solar Cell : Poly-Crystalline 156X44.57mm
- No.of Cells : 36 (4X9)
- Dimensions : 473mm X 670mmX25mm
- Weight : 4.5kgs
- Front Glass : 3.2mm Tempered Glass
- Frame : Anodized Aluminium Alloy
- Junction Box : PV-LH081
- Nominal Operating Cell Temperature : 47°C +/- 2°C



25 Performance
YEARS WARRANTY

INNOVATIVE
German Technology
FIRST TIME IN INDIA

Live Solar Power Generation
FOR INSTANT USE
Standby Storage for Off-Grid Use